





2~42 Core

44~72 Core



Application ::

- .Adopted to Outdoor distribution.
- .Suitable for aerial .pipeline laying method.
- .Long distance and local area network communication

Characteristics ::


- .Steel wire strength.filler protect tube fiber.steel tape armor.
- .Good ultra violet radiation resistant property
- .Good moisture-resistance.

Technical Parameters:

Cable Count	Out sheath Diameter (MM)	Weight (KG)	Minimum allow able Tensile Strength (N)		minimum allow able Crush Load (N/100mm)		Minimum Bending Radius (MM)		Storage temperature (°C)
			short term	long term	short term	long term	short term	long term	
24	10,5	105,00	1500	600	1000	300	20D	10D	-40+60
36	10,5	105,00	1500	600	1000	300	20D	10D	-40+60
42	10,5	105,00	1500	600	1000	300	20D	10D	-40+60
48	12,0	150,00	1500	600	1000	300	20D	10D	-40+60
60	12,0	150,00	1500	600	1000	300	20D	10D	-40+60
72	12,0	150,00	1500	600	1000	300	20D	10D	-40+60



Denominate:



Optical Characteristics

Fiber Sort	Multimode	G.651	A1a:50/125	Graded-index fiber
			A1b:62.5/125	
	Singlemode	G.652(A、B、C、D)		B1.1:Conventional fiber
		G.653		B2: Zero dispersion shifted
		G.654		B1.2 :Cut-off wavelength shifted
		G.655	B4: Main technical data for positive dispersion shifted single-mode fiber	

