



Application ::

- .Adopted to Outdoor distribution.
- .Connected to connectors of various models interconnect.
- .Can be installed conveniently and operated simply.

Characteristics ::

- .More single-core cable design.
- .Steel tape armoured.
- .Waterproof and applicable scurviness environment.

Technical Parameters:

| Cable Count | Out sheath Diameter (MM) | Weight (KG) | Minimum allow able Tensile Strength (N) | | minimum allow able Crush Load (N/100mm) | | Minimum Bending Radius (MM) | | Storage temperature (°C) |
|-------------|--------------------------|-------------|---|-----------|---|-----------|-----------------------------|-----------|--------------------------|
| | | | short term | long term | short term | long term | short term | long term | |
| 2 | 10,5 | 155,00 | 1500 | 600 | 1000 | 300 | 20D | 10D | -40+60 |
| 4 | 10,5 | 155,00 | 1500 | 600 | 1000 | 300 | 20D | 10D | -40+60 |
| 6 | 11,5 | 185,00 | 1500 | 600 | 1000 | 300 | 20D | 10D | -40+60 |
| 12 | 12,5 | 225,00 | 1500 | 600 | 1000 | 300 | 20D | 10D | -40+60 |

Optical Characteristics

| Fiber Sort | Multimode | G.651 | A1a:50/125 | Graded-index fiber |
|------------|------------|---|--------------|----------------------------------|
| | | | A1b:62.5/125 | |
| | Singlemode | G.652(A, B, C, D) | | B1.1:Conventional fiber |
| | | G.653 | | B2: Zero dispersion shifted |
| | | G.654 | | B1.2 :Cut-off wavelength shifted |
| G.655 | | B4: Main technical data for positive dispersion shifted single-mode fiber | | |

