



### Application ::

- .Adopted to indoor disbibution.
- .As pigtail of communication equipment.
- .Suitable for communication equipment served.

### Characteristics ::

- .Adopt optic fiber ribbon as the central unit aramid strength member around.
- .Flexible.easy to peel off.
- .Small bend radius.

### Technical Parameters:

Cable Count (MM)	Outside Diameter (MM)	Weight (KG)	Minimum allowable Tensile Strength (N)		minimum allowable Crush Load (N/100mm)		Minimum Bending Radius (MM)		Storage temperature (°C)
			short term	long term	short term	long term	short term	long term	
2	3.5×2.5	13,00	500	100	500	100	20D	10D	-20+60
4	3.5×2.5	13,00	500	100	500	100	20D	10D	-20+60
6	4.0×2.5	15,00	500	100	500	100	20D	10D	-20+60
8	4.5×2.2	15,00	500	100	500	100	20D	10D	-20+60
12	4.8×2.2	17,00	500	100	500	100	20D	10D	-20+60

### Optical Characteristics

Fiber Sort	Multimode	G.651	A1a:50/125	Graded-index fiber
			A1b:62.5/125	
Singlemode	G.652(A, B, C, D)			B1.1:Conventional fiber
	G.653			B2: Zero dispersion shifted
	G.654			B1.2 :Cut-off wavelength shifted
	G.655			B4: Main technical data for positive dispersion shifted single-mode fiber

