



### Application ::

- .Adopted to indoor distribution..
- .As pigtail of communication equipment.
- .Suitable for communication equipment served.
- .Can be installed conveniently and perated simply.

### Characteristics ::

- .High strength kevlar yarn member
- .High quality tight buffered or loose tube.
- .Soft and easy to strip.
- .Round construction.

### Technical Parameters:

Out sheath Diameter (MM)	Tight buffer Diameter (MM)	Weight (KG)	Minimum allowable Tensile Strength (N)		minimum allowable Crush Load (N/100mm)		Minimum Bending Radius (MM)		Storage temperature (°C)
			short term	long term	short term	long term	short term	long term	
1,6	0,6	2,80	150	80	500	100	20D	10D	-20+60
1,8	0,6	3,00	150	80	500	100	20D	10D	-20+60
2,0	0,9	4,25	150	80	500	100	20D	10D	-20+60
2,4	0,9	5,00	150	80	500	100	20D	10D	-20+60
2,8	0,9	6,60	150	80	500	100	20D	10D	-20+60
3,0	0,9	7,00	150	80	500	100	20D	10D	-20+60

### Denominate:

<b>GJ</b>	<b>F</b>	<b>J</b>	<b>V</b>	
				<b>Sheath Structure Strength member Sort</b>
				GJ: Indoor cable
				F: Non-metal central strength member
				J: Tight buffer
				V: pvc or lszh out sheath



Optical Characteristics				
Fiber Sort	Multimode	G.651	A1a:50/125	Graded-index fiber
			A1b:62.5/125	
	Singlemode	G.652(A、B、C、D)		B1.1:Conventional fiber
		G.653		B2: Zero dispersion shifted
		G.654		B1.2 :Cut-off wavelength shifted
		G.655		B4: Main technical data for positive dispersion shifted single-mode fiber

